


# SINGLE-PHASE SURGE REDUCTION FILTERS 230V, 63A (SRF's)



\* product may be subject to change, please check with Elsafe.

Version: ISSUE 2, 060511, 18.10.2012.



**Elsafe Australia Pty Ltd**

**Sales Enquires**

Tel: +61 (7) 3399 7099

Fax: +61 (7) 3399 9133

Email: [railways@elsafe.com.au](mailto:railways@elsafe.com.au)

**Head Office**

Tel: +61 (2) 9454 7500

Fax: +61 (2) 9454 7505

Email: [railways@elsafe.com.au](mailto:railways@elsafe.com.au)

*service - quality - safety*

[railways.elsafe.com.au](http://railways.elsafe.com.au)

## ELSAFE 230V, 63A SINGLE-PHASE SURGE REDUCTION FILTERS MODEL NUMBERS 570331, 570431, 570531 AND 570631

Elsafe Australia has totally re-engineered and widened its range of rugged, heavy-duty Surge Reduction Filters (SRFs) intended for deployment by Heavy Industry as primary surge protection. They include a combination of high current filtering and surge protection components that have been shown to have extremely low let-through voltages during high current transient testing. Mechanically they have also been independently tested and proven to withstand high vibration environments such as railway trackside installations.

As with all other members of the range, this Surge Reduction Filter comes in 4 distinct variants defined by 2 choices of enclosure, and 2 of customer wiring termination method, all are electrically identical, they are shown in the table below.

MODEL NUMBER/ ORDER CODE	TERMINAL STYLE	ENCLOSURE MATERIAL
570331	10mm STUD	MILD STEEL
570431	10mm STUD	STAINLESS STEEL
570531	CAGE CLAMP	MILD STEEL
570631	CAGE CLAMP	STAINLESS STEEL

Surge protection is implemented on the load side by means of 100kA-rated Metal-Oxide Varistors (MOVs) connected in a “delta” configuration covering active-to-neutral, active-to-earth and neutral-to-earth. The MOV’s themselves are separated from the line side by custom-made inductors wound from solid copper. The inductor chokes are connected in series directly between the line and load terminals to ensure good continuance of supply. A capacitor between active and neutral forms a filter to attenuate any unwanted high frequency harmonics. The active-to-neutral and active-to-earth MOVs are protected by a single resettable thermal cut-out whose purpose is to isolate them in the event of a transient above their rated specifications.

For the purposes of sensing the surge protection status of the SRF through telemetry, a Remote Monitor Board provides a single-pole, double-throw, voltage-free changeover contact. Connection may be made to its normally-open, normally-closed and common terminals<sup>1</sup> by means of a 3-pin screw connector mounted on the PCB, both the normally-open and normally-closed contacts are themselves protected from telemetry line transients by separate MOVs that have a varistor voltage of 470Vdc±10% (300Vac maximum). The Monitor also gives a local indication of the surge protection status by means of an external blue LED indicator fitted to the SRF’s door. The LED may be in any one of the 3 states described below.

### ON STEADY

The supply input is normal and the line-to-neutral and line-to-earth MOV’s are fully connected; the changeover contact is activated (normal).

### FLASHING

The thermal cut-out has operated; the changeover contact is deactivated (in alarm).

### OFF STEADY

A supply failure or Remote Monitor Board fault has developed; the changeover contact is deactivated (in alarm).

<sup>1</sup>here “normal” indicates the state of the contacts when line power is connected to the SRF and the thermal cut-out is in its deactivated state.

## Electrical Specification

<b>RATED LINE VOLTAGE</b>	230Vac		
<b>MAXIMUM APPLIED LINE VOLTAGE</b>	300Vac		
<b>MAXIMUM LOAD CURRENT</b>	63A		
<b>MOV RATING (ALL 3)</b>	470Vdc (300Vac maximum), 100kA		
<b>LOAD-SIDE REMNANT VOLTAGES<sup>2</sup></b>	Active-to-Neutral	720Vdc	
	Active-to-Earth	612Vdc	
	Neutral-to-Earth	744Vdc	
<b>NOMINAL AMPLITUDE FREQUENCY RESPONSE</b>	100% LOAD	Cut-off Frequency	8.6kHz
		Roll-off	40dB/decade
	10% LOAD	Cut-off Frequency	10.2kHz
		Roll-off	40dB/decade
<b>REMOTE MONITOR CONTACT RATINGS</b>	Maximum Applied Voltage <sup>3</sup>	290Vdc/200Vac (MOV-protected)	
	Maximum Current Sink	100mA	
<b>CONNECTION TO CUSTOMER WIRING</b>	Insulator-Mounted 10mm Brass Studs (570331 and 570431)		
	Cage-Clamp Terminals Accepting up to 95mm <sup>2</sup> Conductors (570531 and 570631)		

## Physical Specification

<b>ENCLOSURE DETAILS</b>	
<b>MATERIALS</b>	POWDER-COATED MILD STEEL (570331 and 570531)
	STAINLESS STEEL (570431 and 570631)
<b>INGRESS PROTECTION RATING</b>	IP66

<b>EXTERNAL DIMENSIONS</b>	
<b>HEIGHT</b>	500mm
<b>WIDTH</b>	400mm
<b>DEPTH</b>	210mm

<b>WEIGHT</b>	25kg
---------------	------

## Environmental Specification

<b>AMBIENT TEMPERATURE RANGE</b>	$-20^{\circ}\text{C} \leq T_{\text{amb}} \leq +75^{\circ}\text{C}$
<b>LOCAL RELATIVE HUMIDITY</b>	$\leq 90\%$
<b>VIBRATION TOLERANCE<sup>4</sup></b>	20Hz sinusoidal vibration, 11g peak-to-peak

<sup>2</sup>Compliance with the requirements of AS/NZS61000.4.5 (Surge Immunity) is verified by EMC Technologies Pty Ltd Report Number T110320\_A. The SRF's load-side Remnant Voltages in response to standard 8/20 $\mu$ s, 3kA surges are detailed in that Report.

<sup>3</sup>Both contacts are protected by 6.5kA-rated MOV's each having a varactor voltage of 330Vdc $\pm$ 10% (200Vac maximum)

<sup>4</sup>Vibration Tolerance of all internal SRF connections has been tested by Vipac Engineers and Scientists Ltd as verified in Test Certificate Number 20E-11-0060-COC-463451.